

# TECHNICAL MATERIAL SUBMITTAL

## EMT CONDUIT

**BRAND : YOYA  
UL LISTED**



# YOYA

## UL LISTED EMT

### Electric Metallic Tube Conduit



EMT Conduit-According to ANSI C80.3, UL797

Surface Finishing:Hot Dipped Galvanized Steel

# Features

- Manufactured with high-strength steel, and welded by electric resistance welding process.
- The exterior surface has a clear post-galvanizing coating to provide additional protection against corrosion
- The interior surface provides a smooth continuous raceway for easy and hassle-free wire pulling.
- Both surfaces are free from deflection with a smooth welded seam.
- Excellent ductility, providing uniform bending and cutting in the field
- Consistent Quality for long life: durable, strong, and suitable for bending.

## Specification data

### EMT Conduit-According to ANSI C80.3, UL797 Surface Finishing: Hot Dipped Galvanized Steel

Trade Size	External Diameter	Thickness	Length		Nominal Weight
NPS	MM	MM	Ft	MM	KG/PC
1/2"	17.93	1.07	10	3048	1.36
3/4"	23.42	1.24	10	3048	2.07
1"	29.54	1.45	10	3048	3.06
1-1/4"	38.35	1.65	10	3048	4.55
1-1/2"	44.2	1.65	10	3048	5.28
2"	55.8	1.65	10	3048	6.72
2-1/2"	73.03	1.83	10	3048	9.80
3"	88.9	1.83	10	3048	11.98
3-1/2"	101.6	2.11	10	3048	15.79
4"	114.3	2.11	10	3048	17.80

### IMC Conduit-According to ANSI C80.3, UL797 Surface Finishing: Hot Dipped Galvanized Steel

Trade Size	External Diameter	Thickness Of Wall	Length		Nominal Weight
NPS	MM	MM	Ft	MM	KG/PC
1/2"	20.7	1.98	10	3048	2.79
3/4"	26.1	2.1	10	3048	3.79
1"	32.8	2.35	10	3048	5.38
1-1/4"	41.6	2.41	10	3048	7.10
1-1/2"	47.8	2.54	10	3048	8.65
2"	59.9	2.67	10	3048	11.49
2-1/2"	72.6	3.81	10	3048	19.71
3"	88.3	3.81	10	3048	24.21
3-1/2"	100.9	3.81	10	3048	27.82
4"	113.3	3.81	10	3048	31.38